PRODUCT No. 3556

Internal pump station – 2500 l



(Ilustrative photograph)

Technical data

Material	Polyethylene (PE)
Capacity	2500 l
Weight	250 kg
Pump output	79 l/min (230 V AC)
Length of delivery hose	6 m
Width	2460 mm
Depth	1460 mm
Height	1850 mm

Attributes

- Made of polyethylene by rotary moulding method.
- Double-casing construction – no need of catching basin.
- Simple installation in an open area without further requirements.
- Nominal volume is 95% of overflow volume.
- Resilient to UV radiation and mechanical damage.
- Application – e.g. companies with a smaller vehicle fleet, smaller carriers, garages, depos, etc.
- Dimensions of the product may vary in a range of +/- 1%.

Standard equipment:
Pump 79 l/min / 230 V AC, digital flowmeter K600 B/3, 6 m long delivery hose, automatic delivery nozzle, glass filter with water separator, 2” filling pipe in housing, mechanical safety against overfill (Spill-Stop), liquid level indicator UNIRx (in litres), inner housing leakage indicator, max. level GOK indicator, LED lighting with movement sensor.

Product purpouse

- Designed for vehicle fleets as a pump station. Designed exclusively for diesel fuel. Storage and dispensing of gasoline or other unapproved liquids is prohibited!

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov