PRODUCT No. 3504

Fireproof cabinet with 30 minutes resistance – single wing doors



(Illustrative photograph)

Technical data

Material	High pressurized laminate
Storage capacity	130 l
Containment capacity	20 l
Weight	150 kg
Shelf max. load capacity (evenly distributed)	30 kg
No. (doors/shelves/catching basin)	1 / 3 / 1 pcs
Diameter of air inlet/outlet	100 mm
Width (inner/outer)	491 / 605 mm
Depth (inner/outer)	419 / 550 mm
Height (inner/outer)	1581 / 1980 mm

Attributes

- Construction of the cabinet is made of high pressurized laminate with high chemical resistance.
- Suitable for industry, laboratories, paint shops, hospitals and other similar facilities.
- Designed for regulated storing of flammables and other dangerous substances.
- Provides fire resistance class of 30 minutes resistance.
- Tested in accordance with EN 14470-1, EN 1363-1.
- Doors are lockable by two-point cylindric lock.
- Safety cabinets are obtained with air inlet/outlet of 100 mm diameter.
- Shelves are designed to contain small amount of liquids (catching basins).
- When the 50 °C temperature is exceeded, doors will close by themself.
- Delivered with three shelves and one catching basin on the bottom.

Color variations

- Standardly light grey (RAL 7035).

Product purpouse

- Designed for regulated storing of flammables and other dangerous substances.

Additions

- Shelf can be ordered – type 3504-A (490 x 30 mm).

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov