PRODUCT No. 7382

Sorbent ÖL-EX



(Ilustrative photograph)

Technical data

Material (package)	Polyethylene (PE)
Sorption ability (oil)	23 l
Density	245 g/l
Composition	Polyuretane grit
Package weight	10 kg
Sorption type	Oil
Grain size	0,5 – 4 mm
Width	300 mm
Depth	120 mm
Height	400 mm

Attributes

- Package consists of a polyethylene bag.
- Recycled or waste polyurethane is used for the production of ÖL-EX sorption agents.
- The material is safe according to the REACH directive.
- High sorption capability for oil, grease and oil.
- Does not contain any easily combustible components.
- **Recommended use:** Polyurethane-based loose sorbent for sorption of hazardous liquids – oils, greases, petrol products.

ÖL-EX:
- Oil sorbent for industry, roads and water sources.
- Medium-heavy polyurethane sorbent usable in any weather on roads and waterways.
- Sorbent has a high sorption capacity of mainly oily substances and nearly zero absorption of water.
- Different grain sizes help to clean the oil tracks, are soft and do not damage the treated areas.

Color variations

- Sorbent – beige / gray.

Product purpouse

- Designed for sorption of hazardous liquids – oils, greases and petroleum products.

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov