PRODUCT No. 8017-1

Ground screw




(Ilustrative photograph)

Technical data

Material	Galvanized steel
Weight	1,56 kg
Material thickness	2 mm
For tubes of diameter	24 to 64 mm
Securing screw	M8
Length	550 mm

Attributes

- Made of galvanized steel.
- Suitable for tubes with diameter range of 24 to 64 mm.
- Each screw contains: M8 securing screw, plastic cap, plastic reductions to diameter of tubes 24, 36, 42, 50 and 60 mm



Color variations

- Galvanized.

Product purpouse

- Designed for anchoring of tubes to horizontal soil base.

Additions

- **Use:**
  The ground screw for insertion of tube. Suitable for the construction of fence posts, dryers, garden building or waste bins and others. Suitable for immediate anchoring of the tube into the ground without need for concrete foundation. Easy application with manual device. A rod is inserted into the mounting holes with a diameter of 18 mm and the ground screw is rotated into the ground by rotation so that the entire screw fitting is covered (up to the chamfer). The optimum reduction is selected and inserted into the screw, the tube is than inserted and fixed by pouring gravel into the screw. The soil must be levelled and the screw must be drilled perpendicularly. The length of the screw is chosen according to the length of the tube and the type of soil for stability. The ground screw is removable. The plastic cap protects the inner space of the screw before installation.

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov