PRODUCT No. 8212

Stainless submersible pump with float switch PSDR550X



(Illustrative photograph)

Technical data

Material	Stainless / plastic
Weight	4,9 kg
Max. flow	8,5 m^3/hour
Max. discharge height	7,5 m
Voltage / frequency	230 V / 50 Hz
Output	550 W
Connection	1” - 5/4”
Max. submersion depth	7 m
Switch	float
Min. water height for operation	70 mm
Switching on water level	530 mm
Switching off water level	100 mm
Max. diameter of coarse dirt	5 mm
Max. liquid temperature	35 °C
Cable length	10 m
Protection level	IPX8
Insulation class	B
Dimensions (diameter x height)	150 x 285 mm

Attributes

- Stainless submersible drainage pump with float switch.
- Suitable for draining clean or slightly contaminated drainage water with a max. dirt diameter of up to 5 mm.
- For irrigation, pumping water from cellars, draining pools, pumping of tanks etc.
- For liquids up to 35 °C of temperature.
- Equipped with a 50 Hz single-phase motor and a 10 m long power cable.

Product purpose

- Designed as a submersible pump for pumping clean or slightly contaminated water.

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov