PRODUCT No. 8217

Submersible drainage pump LKS-1008SW



(Ilustrative photograph)

Technical data

Pump:	
Material (body of the pump)	Stainless
Weight	6,2 kg
Max. flow	20 m^3/hour
Max. liquid temperature	35 °C
Max. submersion depth	7 m
Max. discharge	10,5 m
Discharge throat	6/4”
Cable length	10 m
Max. diameter of coarse dirt	35 mm
Dimensions (diameter x height)	183,5 x 392 mm
Motor:	
Voltage	230V, 50 Hz
Output	1000 W
Insulation class	F
Protection level	IPX8

Attributes

- Submersible drainage pump for pumping slightly contaminated water with max. diameter of coarse dirt up to 35 mm.
- Switching on and off is controlled by a float switch with water level monitoring.
- Automatic operation, copper motor winding, built-in motor thermal protection.
- Used for pumping water from flooded cellars, wells, swimming pools, reservoirs, etc.
- For smaller irrigation systems, pumping, retention tanks.
- Equipped with a 10 m long power cable.

Product purpose

- Designed as a submersible drainage pump for pumping slightly contaminated water.

Tel.: 416 823 181
E-mail: info.mevatec@meva.eu

MEVA-TEC s.r.o.
Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov